LANKA WALLTILES PLC

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka. Tel:

+94-11-2808050 Fax: +94-11-2806232

Email: info@lankatiles.com Website: www.lankatiles.com

Factory: Meepe, Padukka. Tel: 0117309804-9

Fax:0112859168 Co. Reg. No. PQ55











TECHNICAL SPECIFICATION

Glazed Ceramic Tiles produced by LANKA WALLTILES PLC comply with ISO 13006:2018 Category B III and ANSI 137.1:2022 Specifications.

Series: Swimming Pool Tiles Color: Blue Tile Type: Corner-FAT-PCMC8-0042-55 Tile Surface: Matt

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE CERAMIC	TEST STATUS
Length & width	1111	ISO 10545-2	+/-0.3%	N/A
Thickness		ISO 10545-2	+/-10.0%	
Straightness of sides		ISO 10545-2	N/A	
Centre curvature		ISO 10545-2	N/A	
Edge curvature	$\Diamond \Diamond$	ISO 10545-2	N/A	
Warpage	\\	ISO 10545-2	N/A	
Rectangularity		ISO 10545-2	N/A	
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES	•	<u> </u>		
Water absorption		ISO 10545-3	7% < E ≤20 %	Comply
Breaking strength		ISO 10545-4	N/A	
Modulus of rupture	TOTAL DE	ISO 10545-4	N/A	
Resistance to surface abrasion-glazed tiles	AURASION RESISTANT	ISO 10545-7	N/A	N/A
Resistance to Thermal shock	II.	ISO 10545-9	N/A	cle sd
Resistance to crazing-glazed tiles	4	ISO 10545-11	1 Cycle passed	1 Cycle Passed
CHEMICAL PROPERTIES	•			
Resistance to staining	STAIN RESISTANT	ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids	CHEMICAL RESISTANT	ISO 10545-13	Min Class GLB	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL	ISO 10545-13	Min Class GLB	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL	ISO 10545-13	Minimum GB	GA
APPLICATIONS	***	Recommended for r ability to be consider	esidential, or commercial swimming pool a ed.	areas. Cleaning

Last Update: 2024-11-06 Prepared By: Executive (QA) Approved By: Manager (QA/RD)

Issue No: 1 Revision No: 0 Date: 2024-11-05