LANKA WALLTILES PLC

LANKA WALLTILES PLC

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka.Tel: +94-11-2808050 Fax: +94-11-2806232 Email: info@lankatiles.com Website: www.lankatiles.com Factory: Meepe, Padukka. Tel: 0117309804-9 Fax:0112859168 Co. Reg. No. PQ55

LANKATILES

Fine Living Redefined



TECHNICAL SPECIFICATION

Glazed Ceramic Floor Tiles produced by LANKA WallTILES PLC comply with ISO 13006:2018(E) Annex J, BS EN 14411:2012 Annex J, Specifications and SLS 1181:2019 standards. Series: Colonize Theme: Heritage

Tile Type: FAH-CLZ---X0813C56

i neme: Heritage			
Tile Size: 45	0x900mm		

Tile Surface: Matt

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE CERAMIC Annex J Group B11a	TEST STATUS
Length & width		ISO 10545-2	+/-0.3%	Comply
Thickness		ISO 10545-2	+/-5.0%	
Straightness of sides	- FF	ISO 10545-2	+/-0.3%	
Centre curvature		ISO 10545-2	+/-0.4%	
Edge curvature		ISO 10545-2	+/-0.4%	
Warpage		ISO 10545-2	+/-0.4%	
Rectangularity		ISO 10545-2	+/-0.3%	
Surface quality	*	ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES			1	
Water absorption		ISO 10545-3	$3 \% < E \le 6 \%$ Individual max 3.3%	Comply
Breaking strength		ISO 10545-4	Not less than 1000 N (Thickness ≥ 7.5mm)	
Modulus of rupture		ISO 10545-4	Min 22 N/ mm ² Individual min 27 N/mm ²	
Resistance to surface abrasion-glazed tiles	ABRASION RESISTANT	ISO 10545-7	Reported abrasion class and cycle passed	Class 3
Resistance to Thermal shock		ISO 10545-9	Required	Comply
Resistance to crazing-glazed tiles	Ø	ISO 10545-11	Required	
CHEMICAL PROPERTIES				
Resistance to staining	STAIN RESISTANT	ISO 10545-14	Minimum class 3	Class 4-5
Resistance to low concentrations of acids	CHEMICAL	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL RESISTANT	ISO 10545-13	Minimum GB	GA
APPLICATIONS			a small amount of scratch dirt. (Residential kit ggias and living area, and terraces).	cchen, halls,

Last Update: 2024-11-06

Prepared By: Executive (QA)

Approved By : Manager (QA/RD)