LANKA WALLTILES PLC

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka. Tel:

+94-11-2808050 Fax: +94-11-2806232

Email: info@lankatiles.com Website: www.lankatiles.com

Factory: Meepe, Padukka. Tel: 0117309804-9

Fax:0112859168 Co. Reg. No. PQ55



Fine Living Redefined









TECHNICAL SPECIFICATION

Glazed Ceramic Floor Tiles produced by LANKA WallTILES PLC comply with ISO 13006:2018(E) Annex J, BS EN 14411:2012 Annex J, Specifications and SLS 1181:2019 standards.

Series: Lasquire Theme: Urban

Tile Type: FAP-LAQ---X0828C56 Tile Size: 300x600mm Tile Surface: Matt

| DIMENSIONS & SURFACE QUALITY | IMAGE | Test methods BS EN ISO | GLAZE CERAMIC Annex J Group B11a | TEST STATUS |
|---|-----------------------|--|--|-----------------|
| Length & width | //// | ISO 10545-2 | +/-0.3% | Comply |
| Thickness | 4 | ISO 10545-2 | +/-5.0% | |
| Straightness of sides | PP | ISO 10545-2 | +/-0.3% | |
| Centre curvature | | ISO 10545-2 | +/-0.4% | |
| Edge curvature | \bigcirc | ISO 10545-2 | +/-0.4% | |
| Warpage | | ISO 10545-2 | +/-0.4% | |
| Rectangularity | | ISO 10545-2 | +/-0.3% | |
| Surface quality | | ISO 10545-2 | Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles. | |
| PHYSICAL PROPERTIES | 1 | <u> </u> | | |
| Water absorption | | ISO 10545-3 | $3\% < E \le 6\%$ Individual max 6.5% | Comply |
| Breaking strength | □ <u>}</u> | ISO 10545-4 | Not less than 1000 N (Thickness ≥ 7.5mm) | |
| Modulus of rupture | | ISO 10545-4 | Min 22 N/ mm ² Individual min 20 N/mm ² | |
| Resistance to surface abrasion-glazed tiles | ABRASION RESISTANT | ISO 10545-7 | Reported abrasion class and cycle passed | Class 3 |
| Resistance to Thermal shock | A‡_ | ISO 10545-9 | Required | Comply |
| Resistance to crazing-glazed tiles | 9 | ISO 10545-11 | Required | |
| CHEMICAL PROPERTIES | | <u> </u> | | |
| Resistance to staining | STAIN RESISTANT | ISO 10545-14 | Minimum class 3 | Class 4 - 5 |
| Resistance to low concentrations of acids | CHEMICAL RESISTANT | ISO 10545-13 | Manufacturer to state classification | Class GLA |
| Resistance to low concentrations of alkalis | CHEMICAL RESISTANT | ISO 10545-13 | Manufacturer to state classification | Class GLA |
| Resistance to household chemicals and swimming pool salts | CHEMICAL | ISO 10545-13 | Minimum GB | GA |
| APPLICATIONS | *** | Normal footwear with low-traffic areas). | a small amount of scratching dirt. (Residential | living area and |

Last Update: 2024-11-06 Prepared By: Executive (QA) Approved By: Manager (QA/RD)

Issue No: 1 Revision No: 0 Date: 2024-11-01