LANKA WALLTILES PLC

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka. Tel:

+94-11-2808050 Fax: +94-11-2806232

Email: info@lankatiles.com Website: www.lankatiles.com

Factory: Meepe, Padukka. Tel: 0117309804-9

Fax:0112859168 Co. Reg. No. PQ55



Fine Living Redefined









TECHNICAL SPECIFICATION

Glazed Ceramic Floor Tiles produced by LANKA WallTILES PLC comply with ISO 13006:2018(E) Annex J, BS EN 14411:2012 Annex J, Specifications and SLS 1181:2019 standards.

Series: Swiral Theme: Spiritual

Tile Type: FAP-SWR---X0830C55 Tile Size: 300x600mm Tile Surface: Matt

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE CERAMIC Annex J Group B11a	TEST STATUS
Length & width	11/1/2	ISO 10545-2	+/-0.3%	Comply
Thickness	4	ISO 10545-2	+/-5.0%	
Straightness of sides		ISO 10545-2	+/-0.3%	
Centre curvature		ISO 10545-2	+/-0.4%	
Edge curvature	\(ISO 10545-2	+/-0.4%	
Warpage		ISO 10545-2	+/-0.4%	
Rectangularity		ISO 10545-2	+/-0.3%	
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES	1	I.		
Water absorption	<u> </u>	ISO 10545-3	$3\% < E \le 6\%$ Individual max 6.5%	Comply
Breaking strength	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	ISO 10545-4	Not less than 1000 N (Thickness ≥ 7.5mm)	
Modulus of rupture		ISO 10545-4	Min 22 N/ mm ² Individual min 20 N/mm ²	
Resistance to surface abrasion-glazed tiles	ABRASION RESISTANT	ISO 10545-7	Reported abrasion class and cycle passed	Class 2
Resistance to Thermal shock	S.	ISO 10545-9	Required	ply
Resistance to crazing-glazed tiles	9	ISO 10545-11	Required	Comply
CHEMICAL PROPERTIES	50 Paris (#21 151)			
Resistance to staining	STAIN RESISTANT	ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL RESISTANT	ISO 10545-13	Minimum GB	GA
APPLICATIONS		Normal footwear with low-traffic areas).	a small amount of scratching dirt. (Residential	living area and

Last Update: 2024-11-06 Prepared By: Executive (QA) Approved By: Manager (QA/RD)

Issue No: 1 Revision No: 0 Date: 2024-11-01