LANKA TILES PLC FO/QA/64

## **LANKA TILES PLC**

215, Nwala Road, Narahenpita, Colombo 05, Sri Lanka.

Tel: +94-11-2808050 Fax: +94-11-2806232

Email: info@lankatiles.com Website: www.lankatiles.com

Factory: St.James Estate, Jaltara, Ranala. Tel: +94 11 2141055 Fax: +94 11 2141045

Co. Reg. No. PQ129

## LANKATILES

Fine Living Redefined

## TECHNICAL SPECIFICATION

SO USO CE SIS

SLS 1181:2019 standards.

Series: Onyx Marble Theme: Mountain Colour: Crystal White

Glazed Porcelain Floor Tiles produced by LANKA TILES PLC comply with ISO 13006:2018(E) Annex H, BS EN 14411:2012 Annex H,

Series: Onyx Marble Theme: Mountain Colour: Crystal White
Tile Type: FAS-ONM---P0035A51 Tile Size: 800x800 mm Tile Surface: Polished

MENSIONS & SURFACE QUALITY IMAGE Test methods CLAZE PORCELAIN

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE PORCELAIN Annex H Group B 1b	TEST STATUS
Length & width	11/1/1	ISO 10545-2	+/-0.3%	Comply
Thickness	Time of the state	ISO 10545-2	+/-5.0%	
Straightness of sides		ISO 10545-2	+/-0.5%	
Centre curvature		ISO 10545-2	+/-0.5%	
Edge curvature	$\Diamond$	ISO 10545-2	+/-0.5%	
Warpage	\\\\\\\\	ISO 10545-2	+/-0.5%	
Rectangularity		ISO 10545-2	+/-0.5%	
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES				
Water absorption		ISO 10545-3	0.5 % < E ≤ 3 % Individual max 3.3%	Comply
Breaking strength		ISO 10545-4	Not less than 1100 N (Thickness ≥ 7.5mm)	
Modulus of rupture	TOTAL STATE	ISO 10545-4	Min 30 N/ mm <sup>2</sup> Individual min 27 N/mm <sup>2</sup>	
Resistance to surface abrasion-glazed tiles	ABRASION RESISTANT	ISO 10545-7	Reported abrasion class and cycle passed	Class 3
Resistance to Thermal shock	II.	ISO 10545-9	Required	Comply
Resistance to crazing-glazed tiles	9	ISO 10545-11	Required	
CHEMICAL PROPERTIES				
Resistance to staining	STAIN RESISTANT	ISO 10545-14	Minimum class 3	Class 4
Resistance to low concentrations of acids	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL	ISO 10545-13	Minimum GB	GA
Phases of Design		☐ Single Face	✓ Multiple Faces	om Faces
APPLICATIONS		small amount of scrat scratch. Ex- Only for of from long periods of	light footwear subject to light traffic with at the ching dirt. Extra care is necessary to protect to domestic usage, bedrooms, living areas. Protect exposure of chemicals and stains. Should not by ways and stairs that are subject to abrasive a	he surface from polished surface be used in areas

Last Update: 2024-10-01 Prepared By : Executive (QA) Approved By : Manager (QA/RD)

Issue No: 1 Revision No: 0 Date: 2024-10-01