LANKA TILES PLC FO/QA/64

## **LANKA TILES PLC**

215, Nwala Road, Narahenpita, Colombo 05, Sri Lanka.

Tel: +94-11-2808050 Fax: +94-11-2806232

Email: info@lankatiles.com Website: www.lankatiles.com

Factory: St.James Estate, Jaltara, Ranala. Tel: +94 11 2141055 Fax: +94 11 2141045

Co. Reg. No. PQ129

## LANKATILES

Fine Living Redefined

## TECHNICAL SPECIFICATION

SO 150 C E SS

SLS 1181:2019 standards.

Series: Venato Marble
Tile Type: FAS-VEM---P0039A51
Theme: Mountain Colour: White
Tile Size: 800x800 mm Tile Surface: Polished

Glazed Porcelain Floor Tiles produced by LANKA TILES PLC comply with ISO 13006:2018(E) Annex H, BS EN 14411:2012 Annex H,

DIMENSIONS & SURFACE QUALITY GLAZE PORCELAIN **IMAGE** Test methods TEST BS EN ISO Annex H **STATUS** Group B 1b Length & width ISO 10545-2 +/-0.3% 11/1 ISO 10545-2 Thickness +/-5.0% Straightness of sides ISO 10545-2 +/-0.5% ISO 10545-2 +/-0.5% Centre curvature ISO 10545-2 Edge curvature +/-0.5% ISO 10545-2 Warpage +/-0.5%ISO 10545-2 Rectangularity +/-0.5% Surface quality ISO 10545-2 Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles. PHYSICAL PROPERTIES Water absorption ISO 10545-3 0.5 % < E < 3 % Individual max 3.3% Breaking strength ISO 10545-4 Not less than 1100 N Comply  $(Thickness \geq 7.5mm)$ Min 30 N/ mm<sup>2</sup> ISO 10545-4 Modulus of rupture Individual min 27 N/mm<sup>2</sup> Reported abrasion class and cycle passed Resistance to surface abrasion-glazed tiles ISO 10545-7 Class 3 Resistance to Thermal shock ISO 10545-9 Required Į; Comply Resistance to crazing-glazed tiles ISO 10545-11 Required CHEMICAL PROPERTIES ISO 10545-14 Minimum class 3 Class 4 Resistance to staining Resistance to low concentrations of acids ISO 10545-13 Manufacturer to state classification Class GLA ISO 10545-13 Class GLA Resistance to low concentrations of alkalis Manufacturer to state classification CHEMICAL Resistance to household chemicals and swimming pool salts ISO 10545-13 Minimum GB GA Phases of Design ▼ Multiple Faces ☐ Single Face □ Random Faces APPLICATIONS Walk on soft-soled or light footwear subject to light traffic with at the most occasional small amount of scratching dirt. Extra care is necessary to protect the surface from scratch. Ex- Only for domestic usage, bedrooms, living areas. Protect polished surface from long periods of exposure of chemicals and stains. Should not be used in areas such as kitchens, entry ways and stairs that are subject to abrasive and slip resistant requirement

Last Update: 2024-10-01 Prepared By : Executive (QA) Approved By : Manager (QA/RD)

Issue No: 1 Revision No: 0 Date: 2024-10-01