

LANKA TILES PLC

215, Nwala Road, Narahenpita, Colombo 05, Sri Lanka.
 Tel: +94-11-2808050 Fax: +94-11-2806232
 Email: info@lankatiles.com Website: www.lankatiles.com
 Factory: St.James Estate, Jaltara, Ranala. Tel: +94 11 2141055 Fax: +94 11 2141045
 Co. Reg. No. PQ129



TECHNICAL SPECIFICATION

Glazed Porcelain Floor Tiles produced by LANKA TILES PLC comply with ISO 13006:2018(E) Annex H, BS EN 14411:2012 Annex H, SLS 1181:2019 standards.

Series: **Riverside**

Theme: **Island Living**

Colour: **Arni**

Tile Type: **FAY-RVE---X0104A52**

Tile Size: **600x600 mm**

Tile Surface: **Gloss**

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE PORCELAIN Annex H Group B 1b	TEST STATUS
Length & width		ISO 10545-2	+/-0.3%	Comply
Thickness		ISO 10545-2	+/-5.0%	
Straightness of sides		ISO 10545-2	+/-0.5%	
Centre curvature		ISO 10545-2	+/-0.5%	
Edge curvature		ISO 10545-2	+/-0.5%	
Warpage		ISO 10545-2	+/-0.5%	
Rectangularity		ISO 10545-2	+/-0.5%	
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES				
Water absorption		ISO 10545-3	0.5 % < E ≤ 3 % Individual max 3.3%	Comply
Breaking strength		ISO 10545-4	Not less than 1100 N (Thickness ≥ 7.5mm)	
Modulus of rupture		ISO 10545-4	Min 30 N/mm ² Individual min 27 N/mm ²	
Resistance to surface abrasion-glazed tiles		ISO 10545-7	Reported abrasion class and cycle passed	Class 3
Resistance to Thermal shock		ISO 10545-9	Required	Comply
Resistance to crazing-glazed tiles		ISO 10545-11	Required	
CHEMICAL PROPERTIES				
Resistance to staining		ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids		ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis		ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts		ISO 10545-13	Minimum GB	GA
Phases of Design		<input type="checkbox"/> Single Face <input type="checkbox"/> Multiple Faces <input checked="" type="checkbox"/> Random Faces		
APPLICATIONS		Recommended for residential floor covering areas subject to normal foot traffic with walk on soft soled or normal foot ware. Ex- Dining rooms, Bedrooms and Living areas. Should not be used in areas such as kitchens, entryways and stairs that are subjected to abrasive and slip resistance requirement.		

Last Update: 2024-10-01

Prepared By : Executive (QA)

Approved By : Manager (QA/RD)