

**LANKA WALLTILES PLC**  
215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka.Tel:  
+94-11-2808050 Fax: +94-11-2806232  
Email: [info@lankatiles.com](mailto:info@lankatiles.com) Website: [www.lankatiles.com](http://www.lankatiles.com)  
Factory: Meepe, Padukka. Tel: 0117309804-9  
Fax:0112859168  
Co. Reg. No. PQ55



**TECHNICAL SPECIFICATION**

Glazed Ceramic Mosaics Tiles produced by LANKA WallTILES PLC comply with ISO 13006:2018 Category B III and ANSI

137.1:2022 Specifications.

Series: **Circular MOSAICS**

Colour: Taupe

Tile Type: **KAWECIR----0238-55**

Sheet Size: 262x262mm

Tile Surface: Matt

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE CERAMIC	TEST STATUS
Length & width		ISO 10545-2	+/-0.3%	N/A
Thickness		ISO 10545-2	+/-10.0%	
Straightness of sides		ISO 10545-2	N/A	
Centre curvature		ISO 10545-2	N/A	
Edge curvature		ISO 10545-2	N/A	
Warpage		ISO 10545-2	N/A	
Rectangularity		ISO 10545-2	N/A	
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
<b>PHYSICAL PROPERTIES</b>				
Water absorption		ISO 10545-3	10% < E ≤20 %	N/A
Breaking strength		ISO 10545-4	N/A	
Modulus of rupture		ISO 10545-4	N/A	
Resistance to surface abrasion-glazed tiles		ISO 10545-7	N/A	N/A
Resistance to Thermal shock		ISO 10545-9	N/A	1 Cycle Passed
Resistance to crazing-glazed tiles		ISO 10545-11	1 cycle passed	
<b>CHEMICAL PROPERTIES</b>				
Resistance to staining		ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids		ISO 10545-13	Min Class GLB	Class GLA
Resistance to low concentrations of alkalis		ISO 10545-13	Min Class GLB	Class GLA
Resistance to household chemicals and swimming pool salts		ISO 10545-13	Minimum GB	GA
<b>APPLICATIONS</b>		Recommended for residential or commercial Wall covering areas Ex- Office area, Kitchens, Corridors.		

Last Update: 2024-11-06

Prepared By: Executive (QA)

Approved By : Manager (QA/RD)