LANKA WALLTILES PLC

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka. Tel:

+94-11-2808050 Fax: +94-11-2806232

Email: info@lankatiles.com Website: www.lankatiles.com

Factory: Meepe, Padukka. Tel: 0117309804-9

Fax:0112859168 Co. Reg. No. PQ55









TECHNICAL SPECIFICATION

Glazed Ceramic Wall Tiles produced by LANKAWall TILES PLC comply with ISO 13006:2018(E) Annex L, BS EN 14411:2012 Annex L Specifications, and SLS 1181:2019 standard.

Series: HEXAGON Theme: Urban

Tile Type: WAP-HEG---X0694B53 Tile Size: 300x600mm Tile Surface: Gloss

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE CERAMIC Annex L Group B111	TEST STATUS
Length & width	///	ISO 10545-2	+/-0.3%	Comply
Thickness		ISO 10545-2	+/-10.0%	
Straightness of sides		ISO 10545-2	+/-0.3%	
Centre curvature		ISO 10545-2	+/-0.4%	
Edge curvature		ISO 10545-2	+/-0.4%	
Warpage	\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	ISO 10545-2	+/-0.4%	
Rectangularity		ISO 10545-2	+/-0.3%	
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES	I	l.		
Water absorption		ISO 10545-3	$10~\% < E \leq 20~\%$ Individual minimum value 9 %	Comply
Breaking strength	□ <u>}</u>	ISO 10545-4	Not less than 600 N (Thickness ≥ 7.5mm)	
Modulus of rupture	Tunna.	ISO 10545-4	Min 12 N/ mm ²	
Resistance to surface abrasion-glazed tiles	ABRASION RESISTANT	ISO 10545-7	Not Applicable for Wall Tile	S
Resistance to Thermal shock	A:	ISO 10545-9	Required	Comply
Resistance to crazing-glazed tiles	9	ISO 10545-11	Required	
CHEMICAL PROPERTIES	.1			
Resistance to staining	STAIN RESISTANT	ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL RESISTANT	ISO 10545-13	Minimum GB	GA
APPLICATIONS	* * *	Recommended for reareas, Kitchens, and C	esidential or commercial Wall covering are Corridors.	eas Ex- Office

Last Update: 2024-11-01 Prepared By: Executive (QA) Approved By : Manager (QA/RD)

Issue No: 1 Revision No: 0 Date: 2024-11-01