LANKA WALLTILES PLC

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka. Tel:

+94-11-2808050 Fax: +94-11-2806232

Email: info@lankatiles.com Website: www.lankatiles.com

Factory: Meepe, Padukka. Tel: 0117309804-9

Fax:0112859168 Co. Reg. No. PQ55











TECHNICAL SPECIFICATION

Glazed Ceramic Wall Tiles produced by LANKAWall TILES PLC comply with ISO 13006:2018(E) Annex L, BS EN 14411:2012 Annex L Specifications, and SLS 1181:2019 standard.

Series: MARIGOLD Theme: Forest

Tile Type: WAP-MRG---X0818A53 Tile Size: 300x600mm Tile Surface: GLOSS

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE CERAMIC Annex L Group	TEST STATUS
Length & width	timi:	ISO 10545-2	B111 +/-0.3%	
	<i>\(\text{\tin}\text{\tetx{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\ti}\}\text{\tetx{\text{\text{\texi}\text{\text{\texi}\text{\text{\text{\text{\ti}\}\tittt{\text{\texititt{\text{\texi}\text{\texit{\text{\text{\ti}\}\tittt{\texititt{\text{\texi}\text{\texit{\text{\tet</i>			Comply
Thickness	4	ISO 10545-2	+/-10.0%	
Straightness of sides		ISO 10545-2	+/-0.3%	
Centre curvature		ISO 10545-2	+/-0.4%	
Edge curvature	\Diamond	ISO 10545-2	+/-0.4%	
Warpage	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	ISO 10545-2	+/-0.4%	
Rectangularity		ISO 10545-2	+/-0.3%	
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES	l .	l	,	
Water absorption		ISO 10545-3	$10~\% < E \leq 20~\%$ Individual minimum value 9 $\%$	Comply
Breaking strength		ISO 10545-4	Not less than 600 N (Thickness ≥ 7.5mm)	
Modulus of rupture		ISO 10545-4	Min 12 N/ mm ²	
Resistance to surface abrasion-glazed tiles	ABRASION RESISTANT	ISO 10545-7	Not Applicable for Wall Tiles	
Resistance to Thermal shock	A1	ISO 10545-9	Required	Comply
Resistance to crazing-glazed tiles	9	ISO 10545-11	Required	
CHEMICAL PROPERTIES	•	l	<u> </u>	
Resistance to staining	STAIN RESISTANT	ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids	CHEMICAL	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL	ISO 10545-13	Minimum GB	GA
APPLICATIONS	**	Recommended for residential or commercial Wall covering areas Ex- Office areas, Kitchens, and Corridors.		

Last Update: 2024-10-01 Prepared By: Executive (QA) Approved By: Manager (QA/RD)

Issue No: 1 Revision No: 0 Date: 2024-10-01