## LANKA WALLTILES PLC

## LANKA WALLTILES PLC

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka.Tel: +94-11-2808050 Fax: +94-11-2806232 Email: info@lankatiles.com Website: www.lankatiles.com Factory: Meepe, Padukka. Tel: 0117309804-9 Fax:0112859168 Co. Reg. No. PQ55

## LANKATILES

Fine Living Redefined



Tile Surface: GLOSS

## **TECHNICAL SPECIFICATION**

Tile Size: 300x600mm

Glazed Ceramic Wall Tiles produced by LANKAWall TILES PLC comply with ISO 13006:2018(E) Annex L, BS EN 14411:2012 Annex L Specifications, and SLS 1181:2019 standard.s Series: POLIS Theme: Urban

Tile Type: WAP-PLS---X0644D53

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE CERAMIC Annex L Group	TEST STATUS
Length & width		ISO 10545-2	B111 +/-0.3%	Comply
Thickness		ISO 10545-2	+/-10.0%	
Straightness of sides		ISO 10545-2	+/-0.3%	
Centre curvature	$\bigotimes \bigotimes$	ISO 10545-2	+/-0.4%	
Edge curvature	$\langle \rangle$	ISO 10545-2	+/-0.4%	
Warpage		ISO 10545-2	+/-0.4%	
Rectangularity		ISO 10545-2	+/-0.3%	
Surface quality	*	ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES			•	
Water absorption		ISO 10545-3	$10\% < E \le 20~\%$ Individual minimum value 9 %	Comply
Breaking strength	_ <u>™</u>	ISO 10545-4	Not less than 600 N (Thickness ≥ 7.5mm)	
Modulus of rupture	tonatis	ISO 10545-4	Min 12 N/ mm <sup>2</sup>	
Resistance to surface abrasion-glazed tiles	AREASTICAN	ISO 10545-7	Not Applicable for Wall Tiles	
Resistance to Thermal shock	<u></u>	ISO 10545-9	Required	ply
Resistance to crazing-glazed tiles	9	ISO 10545-11	Required	Comply
CHEMICAL PROPERTIES	•			
Resistance to staining	STAIN	ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids	CHEMICAL	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL	ISO 10545-13	Minimum GB	GA
APPLICATIONS		Recommended for reareas, Kitchens, and C	esidential or commercial Wall covering are Corridors.	eas Ex- Office

Last Update: 2024-10-01

Prepared By : Executive (QA)