LANKA WALLTILES PLC

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka. Tel:

+94-11-2808050 Fax: +94-11-2806232

 ${\bf Email: info@lankatiles.com\ Web} site: \underline{www.lankatiles.com}$

Factory: Meepe, Padukka. Tel: 0117309804-9

Fax:0112859168 Co. Reg. No. PQ55











TECHNICAL SPECIFICATION

Glazed Ceramic Wall Tiles produced by LANKAWall TILES PLC comply with ISO 13006:2018(E) Annex L, BS EN 14411:2012 Annex L Specifications, and SLS 1181:2019 standard.

Series: Swiral Theme: Spiritual

Tile Type: WAP-SWR---X0830A55Tile Size: 300x600mmTile Surface: Matte

| DIMENSIONS & SURFACE QUALITY | IMAGE | Test methods BS EN ISO | GLAZE CERAMIC Annex L Group B111 | TEST STATUS |
|---|--------------------------|--|--|----------------|
| Length & width | 1111 | ISO 10545-2 | +/-0.3% | Comply |
| Thickness | 4 | ISO 10545-2 | +/-10.0% | |
| Straightness of sides | TY T | ISO 10545-2 | +/-0.3% | |
| Centre curvature | | ISO 10545-2 | +/-0.4% | |
| Edge curvature | \bigcirc | ISO 10545-2 | +/-0.4% | |
| Warpage | ○ | ISO 10545-2 | +/-0.4% | |
| Rectangularity | | ISO 10545-2 | +/-0.3% | |
| Surface quality | * | ISO 10545-2 | Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles. | |
| PHYSICAL PROPERTIES | | 1 | | |
| Water absorption | | ISO 10545-3 | 10 % < E ≤ 20 % | Comply |
| Breaking strength | | ISO 10545-4 | Not less than 600 N (Thickness ≥ 7.5mm) | |
| Modulus of rupture | Tanap. | ISO 10545-4 | Min 12 N/ mm ² | |
| Resistance to surface abrasion-glazed tiles | ABRASION RESISTANT | ISO 10545-7 | Not Applicable for Wall Tile | S |
| Resistance to Thermal shock | <u>I</u> | ISO 10545-9 | Required | Comply |
| Resistance to crazing-glazed tiles | 9 | ISO 10545-11 | Required | |
| CHEMICAL PROPERTIES | u*10.00 € 0.10.00 | | | |
| Resistance to staining | STAIN RESISTANT | ISO 10545-14 | Minimum class 3 | Class 5 |
| Resistance to low concentrations of acids | CHEMICAL RESISTANT | ISO 10545-13 | Manufacturer to state classification | Class GLA |
| Resistance to low concentrations of alkalis | CHEMICAL | ISO 10545-13 | Manufacturer to state classification | Class GLA |
| Resistance to household chemicals and swimming pool salts | CHEMICAL | ISO 10545-13 | Minimum GB | GA |
| APPLICATIONS | *** | Recommended for residential or commercial Wall covering areas Ex- Office areas, Kitchens, and Corridors. | | |

Last Update: 2024-10-01 Prepared By: Executive (QA) Approved By: Manager (QA/RD)

Issue No: 1 Revision No: 0 Date: 2024-10-01