

LANKA WALLTILES PLC
 215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka.Tel:
 +94-11-2808050 Fax: +94-11-2806232
 Email: info@lankatiles.com Website: www.lankatiles.com
 Factory: Meepe, Padukka. Tel: 0117309804-9
 Fax:0112859168
 Co. Reg. No. PQ55






















TECHNICAL SPECIFICATION

Glazed Ceramic Tiles produced by LANKA WALLTILES PLC comply with ISO 13006:2018 Category B III and ANSI 137.1:2022 Specifications.

Series: TRIM FIELDS
Tile Type: Field-Flat

Sheet Size: 196x48mm | 198x98mm | 200x50mm

Tile Surface: Gloss

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE CERAMIC	TEST STATUS
Length & width		ISO 10545-2	+/-0.3%	N/A
Thickness		ISO 10545-2	+/-10.0%	
Straightness of sides		ISO 10545-2	N/A	
Centre curvature		ISO 10545-2	N/A	
Edge curvature		ISO 10545-2	N/A	
Warpage		ISO 10545-2	N/A	
Rectangularity		ISO 10545-2	N/A	
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	
PHYSICAL PROPERTIES				
Water absorption		ISO 10545-3	7% < E ≤ 20 %	Comply
Breaking strength		ISO 10545-4	>600N	
Modulus of rupture		ISO 10545-4	Min 12 N/ mm ²	
Resistance to surface abrasion-glazed tiles		ISO 10545-7	N/A	N/A
Resistance to Thermal shock		ISO 10545-9	10 cycles passed	1 Cycle Passed
Resistance to crazing-glazed tiles		ISO 10545-11	1 Cycle passed	
CHEMICAL PROPERTIES				
Resistance to staining		ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids		ISO 10545-13	Min Class GLB	Class GLA
Resistance to low concentrations of alkalis		ISO 10545-13	Min Class GLB	Class GLA
Resistance to household chemicals and swimming pool salts		ISO 10545-13	— Minimum GB —	GA
APPLICATIONS		Recommended for residential or commercial Wall covering areas Ex- Office area, Kitchens, Corridors.		

Last Update: 2024-11-06

Prepared By: Executive (QA)

Approved By : Manager (QA/RD)