

LANKA TILES PLC

215, Nwala Road, Narahenpita, Colombo 05, Sri Lanka.
 Tel: +94-11-2808050 Fax: +94-11-2806232
 Email: info@lankatiles.com Website: www.lankatiles.com
 Factory: St.James Estate, Jaltara, Ranala. Tel: +94 11 2141055 Fax: +94 11 2141045
 Co. Reg. No. PQ129



TECHNICAL SPECIFICATION

Glazed Vitrified Mosaic Tiles produced by LANKA TILES PLC comply with ISO 13006:2018(E) Annex G, BS EN 14411:2012 Annex G standards.

Series: **60X95 Elongated Hexagon** Colour: - **Sage**
 Tile Type: **KAFCHELO---0006A52** Sheet Size: **268x294 mm** Tile Surface: **Gloss**

DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE VITRIFIED Annex G Group B 1a	TEST STATUS
Mosaic chip length & width		ISO 10545-2	+/-0.5 mm	Comply
Mosaic sheet length & width			+/-1.0 mm	Comply
Thickness		ISO 10545-2	+/-5.0%	6.0 +/-0.2 mm
Surface quality		ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	Comply
PHYSICAL PROPERTIES				
Water absorption		ISO 10545-3	$E_b \leq 0.5\%$ Individual max 0.6%	Comply
Resistance to Thermal shock		ISO 10545-9	min 3 cycles pass	Comply
Resistance to crazing-glazed tiles		ISO 10545-11	10 bars, 1 cycle pass	
Frost resistance		ISO 10545-12	100 cycles pass	Comply
CHEMICAL PROPERTIES				
Resistance to staining		ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids		ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis		ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts		ISO 10545-13	Minimum GB	GA
APPLICATIONS		Mosaic glossy tiles are ideal for bathrooms, kitchens, living rooms, and commercial spaces. They are commonly used for backsplashes, shower walls, and feature walls. However, they are best avoided on floors or steps due to their slippery nature when wet.		

Last Update: 2024-10-01

Prepared By : Executive (QA)

Approved By : Manager (QA/RD)