## LANKA TILES PLC

## LANKA TILES PLC

Thickness

Surface quality

Water absorption

215, Nwala Road, Narahenpita, Colombo 05, Sri Lanka. Tel: +94-11-2808050 Fax: +94-11-2806232 Email: info@lankatiles.com Website: www.lankatiles.com Factory: St.James Estate, Jaltara, Ranala. Tel: +94 11 2141055 Fax: +94 11 2141045 Co. Reg. No. PQ129

## TECHNICAL SPECIFICATION



Fine Living Redefined

LANKATIL

Glazed Vitrified Mosaic Tiles produced by LANKA TILES PLC comply with ISO 13006:2018(E) Annex G, BS EN 14411:2012 Annex G standards. Series. Shape: 40x155 Picket Colour: - Light Grey

Jeries.	
Tile Type:	KAFDHPLO0005B52

Sheet Size: 258x275.75 mm Tile Surface: Gloss **DIMENSIONS & SURFACE QUALITY** Test methods **GLAZE VITRIFIED** IMAGE TEST BS EN ISO Annex G STATUS Group B 1a Mosaic chip length & width ISO 10545-2 +/-0.5 mm 111 Comply Mosaic sheet length & width +/-1.0 mm 1/// Comply ISO 10545-2 +/-5.0% 7.0 +/-0.2 mm ISO 10545-2 Minimum of 95 % of tiles shall be free + from visible defects that would impair Comply the appearance of a major area of tiles. PHYSICAL PROPERTIES <u>.</u> ISO 10545-3  $E_b \le 0.5~\%$ Comply Individual max 0.6% ISO 10545-9 Resistance to Thermal shock min 3 cycles pass Comply Resistance to crazing-glazed tiles ISO 10545-11 10 bars, 1 cycle pass 4

Frost resistance	*	ISO 10545-12	100 cycles pass	Comply
CHEMICAL PROPERTIES				
Resistance to staining	STAIN RESISTANT	ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL RESISTANT	ISO 10545-13	Minimum GB	GA
APPLICATIONS		Mosaic glossy tiles are ideal for bathrooms, kitchens, living rooms, and commercial spaces. They are commonly used for backsplashes, shower walls, and feature walls. However, they are best avoided on floors or steps due to their slippery nature when wet.		

Last Update: 2024-10-01

Prepared By : Executive (QA)

Approved By : Manager (QA/RD)