

**LANKA TILES PLC**

215, Nwala Road, Narahenpita, Colombo 05, Sri Lanka.  
 Tel: +94-11-2808050 Fax: +94-11-2806232  
 Email: [info@lankatiles.com](mailto:info@lankatiles.com) Website: [www.lankatiles.com](http://www.lankatiles.com)  
 Factory: St.James Estate, Jaltara, Ranala. Tel: +94 11 2141055 Fax: +94 11 2141045  
 Co. Reg. No. PQ129



**TECHNICAL SPECIFICATION**

Glazed Vitrified Mosaic Tiles produced by LANKA TILES PLC comply with ISO 13006:2018(E) Annex G, BS EN 14411:2012 Annex G standards.

Series: Tile Type: **KAFFRBLO---0007A52** Shape: **45X95 Bevel** Colour: - **Taupe**  
 Sheet Size: **291x295.5 mm** Tile Surface: **Gloss**

| DIMENSIONS & SURFACE QUALITY                              | IMAGE | Test methods<br>BS EN ISO  | GLAZE VITRIFIED<br>Annex G<br>Group B 1a   | TEST<br>STATUS |
|---|-------|--|--|----------------|
| Mosaic chip length & width                                |       | ISO 10545-2  | +/-0.5 mm  | Comply         |
| Mosaic sheet length & width                               |       |  | +/-1.0 mm  | Comply         |
| Thickness   |       | ISO 10545-2  | +/-5.0%  | 6.5 +/-0.2 mm  |
| Surface quality   |       | ISO 10545-2  | Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles. | Comply         |
| <b>PHYSICAL PROPERTIES</b>                                |       |  |  |                |
| Water absorption  |       | ISO 10545-3  | $E_b \leq 0.5\%$<br>Individual max 0.6%  | Comply         |
| Resistance to Thermal shock                               |       | ISO 10545-9  | min 3 cycles pass  | Comply         |
| Resistance to crazing-glazed tiles                        |       | ISO 10545-11   | 10 bars, 1 cycle pass  |                |
| Frost resistance  |       | ISO 10545-12   | 100 cycles pass  | Comply         |
| <b>CHEMICAL PROPERTIES</b>                                |       |  |  |                |
| Resistance to staining                                    |       | ISO 10545-14   | Minimum class 3  | Class 5        |
| Resistance to low concentrations of acids                 |       | ISO 10545-13   | Manufacturer to state classification   | Class GLA      |
| Resistance to low concentrations of alkalis               |       | ISO 10545-13   | Manufacturer to state classification   | Class GLA      |
| Resistance to household chemicals and swimming pool salts |       | ISO 10545-13   | Minimum GB   | GA             |
| <b>APPLICATIONS</b>                                       |       | Mosaic glossy tiles are ideal for bathrooms, kitchens, living rooms, and commercial spaces. They are commonly used for backsplashes, shower walls, and feature walls. However, they are best avoided on floors or steps due to their slippery nature when wet. |  |                |

Last Update: 2024-10-01

Prepared By : Executive (QA)

Approved By : Manager (QA/RD)