LANKA TILES PLC

LANKA TILES PLC

215, Nwala Road, Narahenpita, Colombo 05, Sri Lanka. Tel: +94-11-2808050 Fax: +94-11-2806232 Email: <u>info@lankatiles.com</u> Website: <u>www.lankatiles.com</u> Factory: St.James Estate, Jaltara, Ranala. Tel: +94 11 2141055 Fax: +94 11 2141045 Co. Reg. No. PQ129

TECHNICAL SPECIFICATION



LANKATILES

Fine Living Redefined

Glazed Vitrified Mosaic Tiles produced by LANKA TILES PLC comply with ISO 13006:2018(E) Annex G, BS EN 14411:2012 Annex G standards.

Series: Pool Tile Type: KAFHSQLOCR-0105A52		Shape:2 Inch SquareColour: -Sheet Size:306x306 mmTile Surface: Gloss		
DIMENSIONS & SURFACE QUALITY	IMAGE	Test methods BS EN ISO	GLAZE VITRIFIED Annex G Group B 1a	TEST STATUS
Mosaic chip length & width		ISO 10545-2	+/-0.5 mm	Comply
Mosaic sheet length & width			+/-1.0 mm	Comply
Thickness		ISO 10545-2	+/-5.0%	6.0 +/-0.2 mm
Surface quality	$\overset{\bullet}{\checkmark}$	ISO 10545-2	Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles.	Comply
PHYSICAL PROPERTIES		•	·	
Water absorption		ISO 10545-3	$E_b \le 0.5 \%$ Individual max 0.6%	Comply
Resistance to Thermal shock		ISO 10545-9	min 3 cycles pass	ply
Resistance to crazing-glazed tiles	G	ISO 10545-11	10 bars, 1 cycle pass	Comply
Frost resistance	*	ISO 10545-12	100 cycles pass	Comply
CHEMICAL PROPERTIES				
Resistance to staining	STAIN RESISTANT	ISO 10545-14	Minimum class 3	Class 5
Resistance to low concentrations of acids	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to low concentrations of alkalis	CHEMICAL RESISTANT	ISO 10545-13	Manufacturer to state classification	Class GLA
Resistance to household chemicals and swimming pool salts	CHEMICAL RESISTANT	ISO 10545-13	Minimum GB	GA
APPLICATIONS		Mosaic pool gloss tiles are ideally applied to pools, waterlines, decorative accents, pool borders, and hot tub walls. Their glossy finish enhances the visual appeal of these vertical surfaces, reflecting light and adding vibrant color. However, they are best avoided on pool floors or steps due to their slippery nature when wet.		

Last Update: 2024-10-01

Prepared By : Executive (QA)

Approved By : Manager (QA/RD)